

NVR604E-32

32 Channel 1.5U 4HDD Network Video Recorders



Key Features

- 32CH IP Video input, up to 12MP
- H.265+/H.265 dual-stream video compression
- Incoming/Outgoing Bandwidth: 256M/256M
- Decoding: 16CH 1080P@30fps/8CH 4M@30fps/6CH 5M@30fps/4CH 4K@30fps
- Supports mainstream cameras of ONVIF and RTSP protocol
- HDMI 1/HDMI 2 asynchronous outputs, maximum resolution of HDMI is 4K
- AI by Camera: SMD, perimeter protection, face detection, etc.



Professional and Reliability

- H.265+ compression effectively reduces storage requirements by up to 75%
- Third-party cloud storage integration -Google Drive and Dropbox for video backup

Stability

- Automatic Network Replenishment

Third-Party Compatibility

- Supports ONVIF and RTSP protocols for seamless integration with third-party cameras

Smart Search and Playback

- Smart search and smart playback for the smart events triggered by humans or vehicles

HD Video Output

- Provide simultaneous HDMI and VGA outputs, and dual asynchronous HDMI outputs

- HDMI video output at up to 4K resolution

Storage and Playback

- Up to 4 SATA interfaces (up to 18 TB capacity per HDD)
- 16-ch synchronous playback

Network & Ethernet Access


- Dual self-adaptive 10/100/1000Mbps Ethernet interface
- Homaxi-view for easy network management

Specification


Video & Audio Input	
IP Video Input	32 ch
Audio Input	1 ch, RCA
Video & Audio Output	
HDMI	HDMI 1: 4K (3840×2160) /30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz HDMI 2: 1920 × 1080/60Hz, 1280 ×1024/60Hz, 1280 × 720/60Hz
VGA	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
Audio Output	2 ch, RCA
Recording	
Compression	H.265+/H.265/H.264+/H.264
Resolution	12MP/8MP/5MP/4MP/3MP/1080P/720P/D1/CIF/QCIF
Playback & Backup	
Playback Resolution	12MP/8MP/5MP/4MP/3MP/1080P/720P/D1/CIF/QCIF
Decoding Capability	2 ch @ 12M 20fps 4 ch @ 8M 30fps 6 ch @ 5M 30fps 8 ch @ 4M 30fps 16 ch @ 1080P 30fps
Synchronous Playback	16 ch
Playback Mode	Smart Playback/Normal/Time Division/Label/Event/Picture Playback
Backup Mode	USB Device/Network/eSATA
Advanced Features	
Smart Detection By Camera	Area Intrusion, Line crossing, Region Entrance /Region Exiting, Fast Moving, Object Missing, Unattended Object, Loitering Detection, Parking Detection, Face Detection, People Gathering Detection, Blurred detection, Scene change detection, Audio exception detection, SMD, PP

Smart Playback	Face detection/Line Crossing/Are Intrusion/Motion Detection/Human Detection/Vehicle Detection
Cloud Storage	Support
Cloud Upgrade	Support
Network	
Incoming Bandwidth	256 Mbps
Outgoing Bandwidth	256 Mbps
Ethernet	2 x RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Protocols	HTTPs, HTTP, TCP/IP, IPv4, UPnP, RTSP, UDP, SMTP, SNMP, Multicast, NTP, DHCP, DNS, IP Filter, DDNS, FTP, P2P, ONVIF
Mobile Surveillance	iOS, Android
Hard Disk	
SATA	4 SATA interface
Capacity	Up to 18TB capacity for each HDD
External Interface	
USB Interface	Front panel: 2 x USB 2.0 Rear panel: 1 x USB 3.0
eSata	1 x eSATA
RS 485	2
Alarm In	16 ch
Alarm Out	4 ch
General	
Operating Conditions	(-10°C ~ 55°C) (14°F ~ 131°F) Humidity 10% to 90%
Power Supply	AC 100~240V
Power Consumption	MAX. 20W (without HDD)
Dimensions (W x D x H)	17.32" x 17.64" x 2.76", 1.5U (440 x 448 x 70 mm)
Gross Weight	13.45 lb (6.1 kg)

Dimensions



Rear Panel



No.	Description	No.	Description
1	Power Switch	6	e SATA Port
2	Power Input	7	VGA Port
3	Ground	8	Audio IN/OUT RCA
4	Alarm Input	9	USB Port
5	HDMI Port	10	Network Port